

TWIN AUGER

15-33 m³

The nine, twin vertical auger mixer wagons, from 15m³ to 33m³, are ideal for operators who want more capacity without extra height, while maintaining quality. Despite the extra capacity, wagons in this range remain easy to manoeuvre.





20mm floor



Rolled walls for superior mixing



Vertical auger with tungsten knives



Extra wide doors for even feeding - 1 m



96% mix consistency



560mm long slat and chain elevator



Features:

- Four weigh bars for consistent and accurate weighing
- Low height single auger to create fluffy mix and reduce hp consumption
- Super single tyres for flotation
- Independent chassis - robust construction
- 20mm base plate, 15mm auger flighting, 8mm hardox walls
- Low flighting auger design
- 560mm long slat and chain discharge elevator
- 4 weigh bars, gold plated
- Hydraulic brakes
- Right and left side doors
- Raised top retaining ring (Rubber extension on VF 2000 T)
- Control switch box for all functions - only 1 DA bank required
- 3 year gearbox warranty



OPTIONS:

- Full hydraulic controls
- Sliding front conveyor
- PVC elevator
- Rear doors
- Front access platform
- Two speed gearbox
- Rear steering axle

	 Capacity (m ³)	 Discharge Height (m)	 Overall Height (m)
VF 1500 T	15	0.72	2.5
VF 1650 T	16	0.8	2.83
VF 2000 T	20	0.8	3.18
VF 2250 T	22	0.9	3.04
VF 2450 T	24	0.9	3.20
VF 2650 T	26	0.9	3.33
VF 2850 T	28	0.9	3.31
VF 3050 T	30	0.9	3.4
VF 3350 T	33	0.9	3.02



CALL FARMGARD 24 HOURS
0800 FARMGARD



EMAIL US FOR MORE INFO
sales@farmgard.co.nz



DOWNLOAD A FREE INFO PACK OR BROCHURE
farmgard.co.nz