
## **FOLDING POWER HARROWS**



## **MAXI-P**

180-450 HP











15° Rotor timing



High resistant side plates



Wide spaced bearings on rotors



**Greaseable top bearings** 



Fully welded gearbed



**Extended Side Plates** 















## **OPTIONS:**

450 hp rated gearbox

Cage Roller

Packer Roller

Kerner cracker packer roller

400mm tines

Tungsten dipped tines

Quick fit tines

Box section rotor protector system

Rotor protectors

Dual lift rams



## Features:

- Fully welded gearbed to give greater rigidity and ensure gears stay "true at all times"
- 15 degree rotor time to reduce horsepower demand and fuel consumption, producing a finer seedbed
- Boron steel tines
- Forged and heat treated one piece rotor shafts
- Greasable top bearings to ensure they have adequate lubrication
- 45 degree moving side plates to ensure flat finish for seedbed preparation
- Hardened gears for long life
- Hydraulic folding with safety locks and 2.5m transport width
- Oil cooler on central and side gearboxes
- Category three linkage, suitable for quickn hitch
- Individual cone shaped rotor protectors
- Rear levelling bar system connected to hydraulic roller with separate winder height adjustment
- Cam clutches on side drive shafts

			44	• •	7
	cm	cm	HP	kg*	Nr
MAXI-P 500	505	500	180 - 450	3000	40
MAXI-P 550	555	550	190 - 450	3230	44
MAXI-P 600	605	600	200 - 450	3470	48
MAXI-P 700	705	700	220 - 450	3900	56

\*weight includes packer roller