

PIONEER 170

110-170 HP

The Celli fixed-width spike rotor harrow has solid boron spikes at an angle that penetrates ground using minimal power. Because it was first designed for stony ground, the machine can take rough conditions. The tailgate traps soil, so it's released as a fine tilth. A suitable seedbed is often created in one pass.





Robust headstock



All gear side drive



Steel face to face rotor seals



Easy drive scroll pattern



Multi position tailgate



Heavy duty gearbox








Features:

- Drive units designed and produced entirely by Celli enabling complete quality control over all componentry and workmanship
- Multi flange waterproof sealing system exclusively by Celli to give rotor bearings full protection from water, dirt, wire and other foreign material
- Steel face to face rotor seals for longer lasting rotor bearings
- Robust headstock for a stronger, longer lasting rotary hoe
- Box section body for rigidity and long life
- Oil filled rotor bearings for low maintenance and guaranteed lubrication
- Four speed gearbox rated up to 170 hp
- Swinging lower links
- Gear side drive
- 250mm working depth
- Side skids
- Two piece adjustable, spring loaded frangor tailgates
- Slip clutch



OPTIONS:

Cage Roller
Packer Roller
Cam clutch
Hydraulic adjustment for rear roller
Hydraulic tailgate adjustment
Rear steel wheels

					
	cm	cm	HP	kg*	Nr
PIONEER 170 F 230	257	230	110 - 170	1240	45
PIONEER 170 F 255	282	255	120 - 170	1320	50
PIONEER 170 F 280	307	280	130 - 170	1390	55
PIONEER 170 F 305	332	305	140 - 170	1470	60

*weight includes packer roller



CALL FARMGARD 24 HOURS
0800 FARMGARD - NZ
1800 FARMGARD - AU



EMAIL US FOR MORE INFO
sales@farmgard.co.nz
sales@farmgard.com.au



DOWNLOAD A FREE INFO PACK OR BROCHURE
farmgard.co.nz
farmgard.com.au