

## TWIN AUGER

20m<sup>3</sup>

The 20m<sup>3</sup> (24m<sup>3</sup> with rubber extension) twin vertical auger mixer wagon is ideal for operators who want more capacity without extra height, while maintaining quality and heavy-duty construction. Despite the extra capacity, the VF2000 is a compact unit, and ideal for chopping high density material. The unique HDM augers are designed to allow quick chopping of dry material or large bales.



Tandem axle option shown above





**Independent chassis to allow for large torque loading**



**20mm floor for extra strength**



**Rolled walls for superior mixing**



**Electric in cab diverter**



**1m wide feed door for even feeding**



**PVC elevator, low maintenance**



## Specifications:

- 20m<sup>3</sup> capacity (24m<sup>3</sup> with rubber extension)
- Twin vertical auger with 7 manganese boron knives per auger
- Single axle with 435/50 x 19.5 lotation tyres
- Right and left side discharge doors
- 1200mm long PVC discharge elevator (mounted on RH door)
- Electric in cab diverter (2 x DA hyd banks required)
- Large counter knives
- Electronic scales with cover over scales
- 4 weigh bars on independant chassis
- Hydraulic brakes
- LED rear lights
- Wide angle PTO shaft with shearbolt protection
- Two speed gearbox with manual changeover handle
- Comer SOM planetary gearboxes, with 3-year warranty
- Rubber top extension
- 3 stage HD winding jack
- Galv ladder mounted on LHS
- 15mm auger lighting
- 8mm ST 52 wall
- 1 year warranty



### OPTIONS:

- Front door with cross conveyor and elevator (as shown above)
- Cable controlled gearbox changeover
- Auger magnets
- Fibre knives
- Hydraulic counter knives
- 22mm augers
- Hardox wear plates
- Chromium-carbide coated knives
- Wall liner
- Tandem axle on springs

Overall height	Overall height without rubber extension	Overall length	Unladen weight
3000mm	2760mm	7000mm	7500kgs
Overall width with elevator open	Distance from wheel to edge of elevator	Tub height	Tub base to ground
3145mm	640mm	2060mm	960mm
Discharge height (elevator down)	Turning circle (hitch to wheel)	Tub top opening length	Overall wheel width
800mm	4680mm	5100mm	2250mm



CALL FARMGARD 24 HOURS  
**1800 FARMGARD**



EMAIL US FOR MORE INFO  
**sales@farmgard.com.au**



DOWNLOAD A FREE INFO PACK OR BROCHURE  
**farmgard.com.au**